

BLUSH REMOVER AND RE-COAT PREP

DESCRIPTION AND USE

Silicate Sealer Remover

- Removes the blush from puddled silicate sealers
- Open the surface to allow duality recoating of a silicate impregnated surface is a product for restoration preparation when a silicated sealer is present. The product is first used to remove all of the sealer prior to cleaning with OneRestore or GS Restoration. Once the sealer has been removed, the cleaning process can be completed.

ADVANTAGES

- * Does not have non-ionics, sulfonates, high pH, harmful solvents, phosphates, or emulsifiers.

TECHNICAL DATA

Appearance & Odor: Amber color, mild citrus odor

Physical State: Liquid

pH: 7.0

Vapor Pressure (mmHg): As water

Vapor Density (air=1): As water

Boiling Point: 212° F

Freezing/Melting Point: N/A

Specific Gravity (water =1): 1.050

Evaporation Rate: As water

Solubility in Water: Complete

PREPARATION

Protect adjacent and surrounding surfaces not intended to be stripped. Cover foliage with polyethylene or other proven protective material.

SURFACE & AIR TEMPERATURES

Excessively high or low temperatures will produce poor results. Best cleaning results are obtained when air and surface temperatures are 40° F or above. Do not clean when temperatures are below freezing or will be overnight. If freezing conditions exist, allow adequate time for surface to thaw. If air temperatures exceed 90° F, flash cool the surface with water before applying product. Do not allow product to dry on a hot surface.

PRE-TESTING

Always test prior to beginning full-scale cleaning operations. Testing should confirm cleaning effectiveness on each type of surface and stain designated to be removed. Testing also determines the desired dwell time and any potential for adverse reactions with adjacent materials. Allow test panels to dry thoroughly before evaluating final appearance and results.

DILUTION

Use undiluted (straight)

APPLICATION INSTRUCTIONS

Use full strength on very heavy silicate sealer. Apply straight (undiluted). Let product dwell for 20 minutes, then pressure wash off. Do not allow product to dry. To test if all of the sealer has been removed, let dry, and apply water droplets. If they bead, repeat the process. If the water sheets and penetrates, you may begin the restoration process.

SAFETY INFORMATION

Precautionary Measures: Always wear goggles and rubber gloves when handling this product. Keep off of skin and clothing. If material comes in contact with clothing, wash before reuse. The product contains Ethanol. Do not get in eyes, on skin or clothing. Avoid breathing fumes. Keep container closed when not in use. Use with adequate ventilation. Applicators should wear a rain suit (plastic, rubber or PVC), boots, gloves, face shields and/or goggles to avoid splash. Dispose of empty containers according to federal, state, and local requirements. Do not use for any other applications other than specified. Do not remove label. Read Material Safety Data Sheet for additional safety and health hazard information prior to use.

SPILL OR LEAK PROCEDURES

Check with the state, local, or federal regulations for waste disposal methods in the area. Wear proper protective equipment while doing cleanup. For large spills, dike and contain for intended use. For small spills, use a chemical absorbent product and place in approved container for disposal.

CONTAINER HANDLING/STORAGE

Store the product in a cool dry place. Vent bung cap before opening. Keep container tightly closed when not in use. Do not use pressure to empty container. Wash thoroughly after handling. Do not use container as dilution or rinsing vessel. Do not cut, grind or weld on or near container. Empty containers retain residue and must be handled as if full.

Store the product in containers with Viton seals or silicon sealant gaskets.



SILICATE SEALER REMOVER

PRODUCT SPECIFICATION
SILICATE SEALER REMOVER

BLUSH REMOVER AND RE-COAT PREP

INSTRUCTIONS IN CASE OF CONTACT OR EXPOSURE

Eyes: Flush thoroughly with water for fifteen minutes. If irritation persists seek medical attention.

Skin: Wash off with water. Neutralize with vinegar. Moisturize skin. If irritation persists, seek medical attention.

Inhalation: Remove to fresh air.

Ingestion: Do not induce vomiting. Drink large amount of water, seek medical attention.

NOTICE

This product has been classified in accordance with the hazard criteria of the CFR.

DISCLAIMER

The information herein is given in good faith, but no warranty, either expressed or implied, is made. Final determination of the suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein we cannot be sure or guarantee these are the only hazards, which exist.

CUSTOMER SERVICE

Factory personnel are available for assistance at 800-313-8505 and will send you additional information on products as necessary.

