

## BRUSHLESS TRUCK WASH

### DESCRIPTION AND USE

Truck Wash Supreme SC is a fast one-step brushless truck wash that is safe on painted surfaces and polished aluminum. The product is an easy, quick rinse and can be spot brushed on heavy stains without leaving brush marks.

### ADVANTAGES

- Versatile truck washing detergent
- Safe on polished aluminum
- No petroleum solvents
- One step brushless system
- Completely biodegradable

### LIMITATIONS

- Not appropriate for most reclaim systems
- Contains D-Limonene (causes rubber to swell)

### TECHNICAL DATA

Appearance & Odor: Clear liquid, mild odor

Physical State: Liquid

pH: 13.5

Vapor Pressure (mmHg): N/A

Vapor Density (air= 1) : >1

Boiling Point: 212° F

Freezing/Melting Point: 32° F

Specific Gravity (water =1): 1.004

Evaporation Rate: <1

Solubility in Water: Complete

### SURFACE & AIR TEMPERATURES

Excessively high or low temperatures will produce poor results and possible harm. Best cleaning results are obtained when air and surface temperatures are 40° Fahrenheit or above. Do not clean when temperatures are below freezing or will be overnight. If freezing conditions exist, allow adequate time for surface to thaw. If air temperatures exceed 90° Fahrenheit, flash cool the surface with water before applying product. Do not allow products to dry on the surface. Always rinse thoroughly while still wet.

### PRE-TESTING

Always test prior to beginning full-scale cleaning operations. Testing should confirm cleaning effectiveness on each type of surface and stain designated to be removed. Testing also determines the desired dwell time and any potential for adverse reactions with adjacent materials. Allow test panels to dry thoroughly before evaluating final appearance and results.

### DILUTION (water to product)

First cut at (4:1) to make product ready to use, then follow the dilution range below:

- (10:1) for general or routine cleaning
- (4:1) for quick, one application cleaning including de-oxidizing aluminum with maximum dwell time of 1 minute then rinse before the product dries.

Note: Dilutions will vary based on the severity of the stain and the type of surface.

### APPLICATION INSTRUCTIONS

Truck Wash Supreme SC is designed for use with a pressure washer. Apply, up or downstream using high or low pressure application with hot or cold water.

- For quick, one application cleaning, apply the product at the proper dilution, with a one minute maximum dwell time. For general or routine cleaning, apply the product at the proper dilution. The product must be applied using two quick applications, spaced several minutes apart without rinsing between applications. Rinsing: Craftsmanship determines the appropriate pressures for rinsing. High pressure rinsing is recommended approximately 1000 - 2000 psi with a wide angle nozzle. When using the quick one application method, be prepared to rinse within one minute. Do not allow product to dry before rinsing thoroughly. Water softeners are built into the product; water re-treatment is generally not necessary.

Note: If Truck Wash Supreme is used on vehicles that have been washed with certain silicates a white film may result. If this occurs a solution of Sabre diluted 4:1 and brushed on is generally effective at remedying this situation.

### SAFETY INFORMATION

Precautionary Measures: Always wear goggles and rubber gloves when handling this product. Keep off of skin and clothing. If material comes in contact with clothing, wash before reuse. The product contains Ethanol, Potassium Hydroxide, and Tetrasodiumsalt of Ethylenediaminetetracetic Acid. Do not get in eyes, on skin or clothing. Avoid breathing fumes. Keep container closed when not in use. Use with adequate ventilation. Applicators should wear rain suit (plastic, rubber or PVC), boots, gloves, face shields and/or goggles to avoid splash to bare skin and eyes. Dispose of empty containers according to federal, state and local requirements. Do not use for any other applications other than specified. Do not remove label. Read Material Safety Data Sheet for additional safety and health hazard information prior to use.



## BRUSHLESS TRUCK WASH

### SPILL OR LEAK PROCEDURES

Check with the state, local, or federal regulations for waste disposal methods in the area. Wear proper protective equipment while doing cleanup. For large spills, dike and contain for intended use. For small spills, use a chemical absorbent product and place in approved container for disposal.

### CONTAINER HANDLING/STORAGE

Store the product in a cool, dry place away from acids. Keep container tightly closed when not in use. Do not use pressure to empty container. Wash thoroughly after handling. Do not use container as dilution or rinsing vessel. Empty containers retain residue and must be handled as if full. Store the product in containers with Viton seals or silicon sealant gaskets.

### INSTRUCTIONS IN CASE OF CONTACT OR EXPOSURE

Eyes: Flush with water for fifteen minutes. If irritation persists consult physician.  
Skin: Flood with water. If irritation develops, call physician.  
Inhalation: N/A  
Ingestion: Drink large amounts of water. Seek medical attention.

### NOTICE

This product has been classified in accordance with the hazard criteria of the CFR.

### DISCLAIMER

The information herein is given in good faith, but no warranty, either expressed or implied, is made. Final determination of the suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot be sure or guarantee these are the only hazards which exist.

### CUSTOMER SERVICE

Factory personnel are available for assistance at 800-313-8505 and will send you additional information on products as necessary.

