

NON-HAZARDOUS LOW ODOR LIQUID STRIPPER

DESCRIPTION AND USE

- * Removes ink, marker and graffiti from interiors, painted surfaces and fiberglass.
- * Removes decal adhesive from trucks, ATMs and sensitive surfaces.
- * Removes silicone caulk and sealer from sensitive surfaces.

ADVANTAGES

- * Will not harm most substrates
- * Mild on skin
- * Non-flammable and biodegradable
- * Will not raise the grain of wood or cause flash rusting on metal

LIMITATIONS

- * Will not work on epoxy or urethane type coatings
- * Do not use on Plexiglas. (Use Plexi-Clean).

TECHNICAL DATA

Appearance & Odor: White to yellow over time, mild citrus odor.

Physical State: liquid

pH: 7.5

Vapor Pressure (mmHg): N/A

Vapor Density (air=1): N/A

Boiling Point: 212 °F

Freezing/Melting Point: N/A

Specific Gravity (water =1): 0.900

Evaporation Rate: N/A

Solubility in Water: Forms a milky white emulsion

PREPARATION

Protect adjacent and surrounding surfaces not intended to be stripped. Cover foliage with polyethylene or other proven protective material.

SURFACE & AIR TEMPERATURES

Excessively high or low temperatures will produce poor results and possible harm. Best cleaning results are obtained when air and surface temperatures are 40° F or above. Do not clean when temperatures are below freezing or will be overnight. If freezing conditions exist, allow adequate time for surface to thaw. If air temperatures exceed 90° F, flash cool the surface with water before applying product. Do not allow product to dry on a hot surface.

PRE-TESTING

Always test prior to beginning full-scale cleaning operations. Testing should confirm cleaning effectiveness on each type of surface and stain designated to be cleaned. Test also to determine the desired surface contact time and any potential for adverse reactions with adjacent materials. Allow test panels to dry thoroughly before evaluating final appearance and results.

DILUTION

Use undiluted.

APPLICATION INSTRUCTIONS

Graf-Ex is used straight. Apply with a low pressure spray unit or wipe on using a cloth. Spray product on from the top down in an overlapping, side to side motion. A damp cloth is often all that is necessary to remove paint or ink. The material works better at an ambient temperature of 70° Fahrenheit range. Occasionally two applications (one following the other after a short soak time) will out perform a single application and mechanical removal. The material penetrates very quickly. Dwell times will vary with the thickness of the coating to be stripped. Graf-Ex can remove most materials in fifteen minutes. Craftsmanship determines the appropriate pressures for rinsing. A thorough rinse job is always recommended, however, our chemistry never requires flooding a wall. Pressures that mark or damage the surface should be avoided. When in doubt, follow the manufacturers recommended P.S.I. for the substrate on which you are working. Proper ventilation should always be used when working indoors. It is recommended that skin contact be kept to a minimum and at least a water rinse after contact.

COVERAGE RATES

Coverage rates will vary from 100 - 250 sq. ft. per gallon depending on the surface porosity, texture and severity of staining.

SAFETY INFORMATION

Precautionary Measures: Always wear goggles and gloves when handling this product. Keep off of skin and clothing. If material comes in contact with clothing, wash before reuse. The product contains Hydrocarbon Blend Naptha. Do not get in eyes, on skin or clothing. Avoid breathing fumes. Keep container closed when not in use. Use with adequate ventilation. Applicators should wear boots and gloves, face shields and/or goggles made out of solvent resistant materials to avoid splash to bare skin and eyes. Use NIOSH/MSHA approved respiration



NON-HAZARDOUS LOW ODOR LIQUID STRIPPER

if over P.E.L. and adequate ventilation is not provided. Take precautions to avoid exposing building occupants to odor when it is a problem. Dispose of empty containers according to federal, state and local requirements. Avoid drifting of material or rinse water onto autos and pedestrians by protecting or diverting such traffic. Do not dilute Graf-Ex with any other product. Do not use for any other applications other than specified. Do not remove label. Read Material Safety Data Sheet for additional safety and health hazard information prior to use.

SPILL OR LEAK PROCEDURES

Check with the state, local, or federal regulations for waste disposal methods in the area. Wear proper protective equipment while doing cleanup. For large spills, dike and contain for intended use. For small spills, use a chemical absorbent product and place in approved container for disposal.

CONTAINER HANDLING/STORAGE

Store the product in a cool dry place. Do not allow this product to freeze. Vent bung cap before opening. Keep container tightly closed when not in use. Wash thoroughly after handling. Empty containers retain residue and vapors and must be handled as if full. Completely rinse drum prior to disposal.

INSTRUCTIONS IN CASE OF CONTACT OR EXPOSURE

Eyes: Flood with water for fifteen minutes. If irritation persists, call physician.

Skin: Wash off with soap and water. If irritation develops call physician

Inhalation: Do not induce vomiting. Seek immediate medical attention

Ingestion: Remove to fresh air. If irritation develops, call physician.

NOTICE

This product has been classified in accordance with the hazard criteria of the CFR.

DISCLAIMER

The information herein is given in good faith, but no warranty, either expressed or implied, is made. Final determination of the suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein we cannot be sure or guarantee these are the only hazards, which exist.

CUSTOMER SERVICE

Factory personnel are available for assistance at 800-313-8505 and will send you additional information on products as necessary

