

BRUSHLESS TRUCK WASH

DESCRIPTION AND USE

Supreme BC is a brushless, spot-free drying fleet and vehicle wash that is safe on painted surfaces including polished aluminum. Supreme BC leaves a great shine after removing virtually any dirt, soil or stain. It also works hot or cold, but should not exceed 120 degrees F.

ADVANTAGES

- * Safe on polished aluminum
- * Brushless with a spot-free rinse
- * Concentrated Cleaner
- * Biodegradable

LIMITATIONS

- * Not appropriate for most reclaim systems

TECHNICAL DATA

Appearance & Odor: Amber color, mild citrus odor.

Physical State: Liquid

pH: 13.5

Vapor Pressure (mmHg): As Water

Vapor Density (air=1): As Water

Boiling Point: 212 ° F

Freezing/Melting Point: N/A

Specific Gravity (water =1): 1.11

Evaporation Rate: As water

Solubility in Water: Complete

SURFACE & AIR TEMPERATURES

Excessively high or low temperatures will produce poor results and possible harm. Best cleaning results are obtained when air and surface temperatures are 40° Fahrenheit or above. Do not clean when temperatures are below freezing or will be overnight. If freezing conditions exist, allow adequate time for surface to thaw. If air temperatures exceed 90° Fahrenheit, flash cool the surface with water before applying product. Do not allow product to dry on a hot surface.

PRE-TESTING

Always test prior to beginning full-scale cleaning operations. Testing should confirm cleaning effectiveness on each type of surface and stain designated to be removed. Testing also determines the desired dwell time and any potential for adverse reactions with adjacent materials. Allow test panels to dry thoroughly before evaluating final appearance and results.

DILUTION

First cut at 4:1 to make product ready to use then follow the dilution range listed below. Apply using pressure washer - up or down stream or low pressure spray applicator.

- 10:1 for fleet washing
- 20:1 for general or vehicle washing
- 50:1 Brush and new car cleanup...
- Below 10:1 is a brushing dilution or low pressure for spraying (extreme cases or for degreasing frames).
- 8:1 Whitewall with brushes.
- 3:1 Whitewall without brushes.

Note: Dilutions will vary based on the severity of the stain and type of surface.

APPLICATION INSTRUCTIONS

Supreme BC is designed for use with a pressure washer, high or low pressure application, using hot or cold water. The product must be laid on the surface using two quick applications which leads to soil release. Craftsmanship determines the appropriate pressure for rinsing. A thorough rinse is always recommended. Pressures that mark or damage the surface should be avoided. Water re-treatment is generally not necessary; water softeners are built into the product.

SAFETY INFORMATION

Precautionary Measures: Always wear goggles and rubber gloves when handling this product. Keep off of skin and clothing. If material comes in contact with clothing, wash before reuse. Do not get in eyes, on skin or clothing. Avoid breathing fumes. Keep container closed when not in use. Use with adequate ventilation. Applicators should wear boots, gloves, face shields, and/or goggles to avoid splash to bare skin and eyes. Dispose of empty containers according to federal, state and local requirements. Do not use for any other applications other than specified. Do not remove label. Read Material Safety Data Sheet for additional safety and health hazard information prior to use.

SPILL OR LEAK PROCEDURES

Check with the state, local or federal regulations for waste disposal methods in your area. Wear proper protection equipment while doing cleanup. Large spills - dike and contain for intended use. Small spills - use chemical spill absorbent product and place in approved container for disposal.



BRUSHLESS TRUCK WASH

CONTAINER HANDLING/STORAGE

Store the product in a cool dry place away from acids. Keep container tightly closed when not in use. Do not use pressure to empty container. Wash thoroughly after handling. Do not use container as dilution or rinsing vessel. Empty containers retain residue and must be handled as if full. Store product in containers with Viton seals or silicon sealant gaskets.

INSTRUCTIONS IN CASE OF CONTACT OR EXPOSURE

Eyes: Flood with water for fifteen minutes. Seek immediate medical attention.

Skin: Wash off with water. Neutralize with vinegar. Re-oil skin. If irritation persists, seek medical attention.

Inhalation: Remove to fresh air.

Ingestion: Drink large amounts of water. Do not induce vomiting. Seek medical attention.

NOTICE

This product has been classified in accordance with the hazard criteria of the CFR.

DISCLAIMER

The information herein is given in good faith, but no warranty, either expressed or implied, is made. Final determination of the suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein we cannot be sure or guarantee these are the only hazards, which exist.

CUSTOMER SERVICE

Factory personnel are available for assistance at 800-313-8505 and will send you additional information on products as necessary.

