

WASH ON WET WAX

DESCRIPTION AND USE

W.O.W.W. is a wash and wax type product that is safe for all surfaces. The clean extends to hard-to-remove problems such as tree sap and road oils. W.O.W.W. is a good non-abrasive polish for aluminum and chrome surfaces on cars.

ADVANTAGES

- Safe for all surfaces
- Exceptionally mild product with a pleasant odor
- Not build up or haze
- Leaves a shine and beading that lasts for weeks.
- Completely biodegradable

LIMITATIONS

- Product effectiveness limited when frozen

TECHNICAL DATA

Appearance & Odor: Light amber liquid, mild odor.

Physical State: Liquid

pH: 4.0

Vapor Pressure (mmHg): N/A

Vapor Density (air=1): N/A

Boiling Point: 212° F

Freezing/Melting Point: 20° F

Specific Gravity (water =1): 1.140

Evaporation Rate: N/A

Solubility in Water: Complete

SURFACE & AIR TEMPERATURES

Excessively high or low temperatures will produce poor results and possible harm. Best cleaning results are obtained when air and surface temperatures are 40° Fahrenheit or above. Do not clean when temperatures are below freezing or will be overnight. If freezing conditions exist, allow adequate time for surface to thaw. If air temperatures exceed 90° Fahrenheit, flash cool the surface with water before applying product. Do not allow products to dry on the surface. Always rinse thoroughly while still wet.

PRE-TESTING

Always test prior to beginning full-scale cleaning operations. Testing should confirm cleaning effectiveness on each type of surface and stain designated to be removed. Testing also determines the desired dwell time and any potential for adverse reactions with adjacent materials. Allow test panels to dry thoroughly before evaluating final appearance and results.

DILUTION

- Use undiluted (straight) for badly hazed finishes
- 10:1 - 30:1 for weekly washing or light duty cleaning.

APPLICATION INSTRUCTIONS

W.O.W.W. can be applied by low pressure application with a spray unit, squirt bottle, brush, mop, or through a pressure washer. The range of dilutions runs from straight for badly hazed finishes to higher dilutions for better shine. Apply the product, starting at the bottom and working to the top, and from end to end. Do not let the product dry on the surface. Very little dwell time is needed for shine. Follow with a clear water rinse. There will be immediate beading. Sap and stain removal require a prolonged dwell time. If the product dries, apply again to reset the finish before rinsing. Dwell times will vary with surface and soil. Test for the appropriate dilution and dwell time.

SAFETY INFORMATION

Precautionary Measures: Always wear goggles and rubber gloves when handling this product. Keep off of skin and clothing. If material comes in contact with clothing, wash before reuse. The product contains Trithhanolamine and d-limonene. Do not get in eyes, on skin or clothing. Avoid breathing fumes. Keep container closed when not in use. Use with adequate ventilation. Applicators should wear (plastic, rubber or PVC) boots, gloves, face shields and/or goggles to avoid splash to bare skin and eyes. Dispose of empty containers according to federal, state and local requirements. Do not use for any other applications other than specified. Do not remove label. Read Material Safety Data Sheet for additional safety and health hazard information prior to use.

SPILL OR LEAK PROCEDURES

Check with the state, local, or federal regulations for waste disposal methods in the area. Wear proper protective equipment while doing cleanup. For large spills, dike and contain for intended use. For small spills, use a chemical absorbent product and place in approved container for disposal.

CONTAINER HANDLING/STORAGE

Store the product in a cool, dry place away from alkali/base. Do not allow this product to freeze. Vent bung cap before opening. Keep container tightly closed when not in use. Wash thoroughly after handling. Empty containers retain residue and vapors and must be handled as if full. Completely rinse drum prior to disposal. Store the product in containers with Viton seals or silicon sealant gaskets.



W.O.W.W.

PRODUCT SPECIFICATION
W.O.W.W.

WASH ON WET WAX

INSTRUCTIONS IN CASE OF CONTACT OR EXPOSURE

Eyes: Flush thoroughly with water for fifteen minutes. If irritation persists, seek medical attention.

Skin: Wash off with water. Re-oil skin. If irritation persists, seek medical attention.

Inhalation: Remove to fresh air.

Ingestion: Do not induce vomiting. Drink large amounts of water. Seek medical attention.

NOTICE

This product has been classified in accordance with the hazard criteria of the CFR.

DISCLAIMER

The information herein is given in good faith, but no warranty, either expressed or implied, is made. Final determination of the suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot be sure or guarantee these are the only hazards which exist.

CUSTOMER SERVICE

Factory personnel are available for assistance at 800-313-8505 and will send you additional information on products as necessary.

