

## BRUSHLESS TRUCKWASH

### DESCRIPTION AND USE

SIZZLE is brushless pressure wash soap. SIZZLE truck wash system is versatile in the ways it may be applied: low or high pressure as well as through foaming arch. High-pressure application will give faster performance and higher dilutions. The product works best when heated, also functions well cold. The water softeners are built in and are to be used to the greatest advantage if premixed at high dilutions before application. A pressure rinse is recommended with the SIZZLE.

### ADVANTAGES

\* High dilutions

### LIMITATIONS

\* Not safe on polished aluminum, passable with a quick rinse

### TECHNICAL DATA

Appearance & Odor: Brown color, mild odor

Physical State: liquid

pH: 13.5

Vapor Pressure (mmHg): As water

Vapor Density (air=1): As water

Boiling Point: 210°F

Freezing/Melting Point: N.A.

Specific Gravity (water =1): 1.12

Evaporation Rate: As water

Solubility in water: Complete

### SURFACE & AIR TEMPERATURES

Excessively high or low temperatures will produce poor results and possible harm. Best cleaning results are obtained when air and surface temperatures are 40° F or above. Do not clean when temperatures are below freezing or will be overnight. If freezing conditions exist, allow adequate time for surface to thaw. If air temperatures exceed 90° F, flash cool the surface with water before applying product. Do not allow product to dry on a hot surface.

### PRE-TESTING

Always test prior to beginning full-scale cleaning operations. Testing should confirm cleaning effectiveness on each type of surface and stain designated to be removed. Testing also determines the desired dwell time and any potential for adverse reactions with adjacent materials. Allow test panels to dry thoroughly before evaluating final appearance and results.

### DILUTION

- 20:1 low pressure brushless.
- 30:1 high pressures brushless
- 100:1 brushing application

### APPLICATION INSTRUCTIONS

This product may be applied downstream or upstream through a pressure washer. You can use a low pressure applicator or by brushing. Rinsing is best with a pressure washer for brushless clean or with a garden hose after brushing. Do not allow the product to dry on the glass.

### SAFETY INFORMATION

Precautionary measures: Always wear goggles and rubber gloves when handling this product. Keep off of skin and clothing. If material comes in contact with clothing, wash before reuse. It is important to wear eye protection at all times when handling this product. Do not get in eyes, on skin or clothing. Keep container closed when not in use. Do not allow product to freeze. Do not remove label. Read Material Safety Data Sheets for additional safety and health hazard information prior to use.

### SPILL OR LEAK PROCEDURES

Check with the state, local, or federal regulations for waste disposal methods in the area. Wear proper protective equipment while doing cleanup. For large spills, dike and contain for intended use. For small spills, use a chemical absorbent product and place in approved container for disposal.

### CONTAINER HANDLING AND STORAGE

Precautions to be taken in handling and storage: Keep container closed when not in use, store in a cool dry place. Other Precautions: Store away from acids.

### DISCLAIMER

The information herein is given in good faith, but no warranty, either expressed or implied, is made. Final determination of the suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein we cannot be sure or guarantee these are the only hazards, which exist.

### INSTRUCTIONS IN CASE OF CONTACT OR EXPOSURE

Eyes: Flush thoroughly with water for fifteen minutes. If irritation persists, seek medical attention.



# SIZZLE

PRODUCT SPECIFICATION  
SIZZLE

## BRUSHLESS TRUCKWASH

Skin: Wash off with soap and water. Moisturize skin. If irritation persists, seek medical attention.

Ingestion: Do not induce vomiting. Drink large amounts of water. Seek medical attention.

Inhalation: Remove to fresh air.

### NOTICE

This product has been classified in accordance with the hazard criteria of the CFR.

### CUSTOMER SERVICE

Factory personnel are available for assistance, call 1-800-313-8505.

---

EaCo Chem. Inc.  
765 COMMERCE AVE  
NEW CASTLE PA 16101

PHONE: (724) 656-1055  
FAX: (724) 656-0757  
[www.eacochem.com](http://www.eacochem.com)

